

KL 60



The KL60 tread pattern is primarily designed for high traction performance. Its contemporary open tread design allows self-cleaning while the transverse solid block greatly improves stability and off-road handling.

As in all GIIB Supercool revolutionary tread pattern, enhanced safety is a standard feature and the hallmark of German Engineering excellence.





KL 60

TECHNICAL SPECIFICATION

FEATURES



- Cood transmission of traction forces particularly on unpaved surfaces
- >>> Very good selfcleaning due to open tread design
- >>> Cut and tear resistant due to specially formulated compound

Width		Depth	
(mm)	(inch)	(mm)	(inch)
140	5 ¹ / ₂	12.0	¹⁵ / ₃₂
150	5 ⁷ / ₈	12.0	¹⁵ / ₃₂
160	6 ¹ / ₄	13.0	¹⁶ / ₃₂
170	6 ⁵ / ₈	14.0	¹⁸ / ₃₂
180	7 ¹ / ₁₆	16.5	²¹ / ₃₂
185	7 ¹ / ₄	16.5	²¹ / ₃₂
190	7 ³ / ₈	16.5	²¹ / ₃₂
195	7 ⁵ / ₈	16.5	²¹ / ₃₂
200	7 7/8	17.0	²¹ / ₃₂
215	8 ⁷ / ₁₆	18.0	²³ / ₃₂
220	8 ⁵ / ₈	19.0	²⁴ / ₃₂
230	9	19.0	²⁴ / ₃₂
240	9 3/8	19.0	²⁴ / ₃₂
250	9 ⁷ / ₈	21.0	²⁶ / ₃₂

Allow 3% commercial tolerance









